



NEW!

LLUB (Long life Ultra Bright) Green led Backlight 100x100

LESS THAN 20% LUMINANCE LOSS AFTER 100 000 HOURS (*)
LESS THAN 10% CHROMATICITY SHIFT AFTER 100 000 HOURS (*)

00000675 : PHLOX - LEDG - BL - 100x100 - LLUB - Q - 1R - 24V



Illumination

Luminance minimum	≥35 000 cd/m ² continuous mode
Uniformity minimum	≥ 95% (+/- 10%)
Source Type	Green LED
Wave Length	525 nm (±5 nm)
Light Angular Distribution	30° 1/2 angle
Expected Life	> 100 000 hours

Scan for DS
and 3D Files !



Electrical

Input Voltage	24 VDC (continuous mode)
Input Current	≤600 mA (continuous mode)
Cable length	2 M - Ø 2.7 mm (6.56 ft - Ø 0.10")
Connector	None
Cable pinout	None
CE Conformity	Yes
Strobe mode	Available in option

Outer unit

L x W x H	140 x 134 x 8.5 mm (5.51 x 5.28 x 0.334")
Housing Material	Black Anodized Aluminium
Weight	400 g (14.1 oz)
Mounting	4 bore holes (D7,2mm for the first 3.5mm of height, D4 for the other 5 mm).

LLUB Backlights by PHLOX® offer the best life cycle, the best chromaticity stability and the best luminance on the market, all in an ultra compact and IP-63 body. PHLOX® is the only manufacturer to provide uniformity and luminance datas on the quality control seal positioned at the back of every backlight.

DESIGNED

FOR YOUR APPLICATION

- Bottle inspection (glass and plastic)
- Particle measurement
- Picture digitalization
- Dimensional control
- Shaping control
- Quality control with transparency.


& YOUR INDUSTRIAL SECTOR

- Glassmaking
- Pharmaceutical/Cosmetics
- Automotive
- Agribusiness
- Electronics
- Aeronautics and space.

Environmental

Max. Operating Humidity	95% non-condensing
Operating Temperature	50°C (122°F) max
Storage Temperature	60°C (140°F) max
Shelf life	12 months from date of purchase
Max.temp.on housing	+80°C (+176°F)

area of temperature measurement
30mm all along the edges of the back of
the black anodized aluminium housing
(see image)



Do not cover the backlight when it's switched on.

Accessories

LED Dimmer: 28V-5A very compact and easy to use
Product key: PHLOX DIM LIGHT



Power supply: 110V and 220V

Product key: ALIM-24V-2.5A60WEU or ALIM-24V-2.5A60WUS


CLASS 0: NO RISK (CIE S2009:2002/NF EN 62471)

RoHS directive compliant

Each PHLOX Backlight is provided with:

- 24 months warranty
- Certificate of uniformity and luminance
- Seal of quality on the back

January 15th, 2025



PROPRIÉTÉ DE PHLOX SA- REPRODUCTION INTERDITE SAUF ACCORD ÉCRIT

00000675 : PHLOX-LEDG-BL-100X100-LLUB-Q-1R-24V

TEL: 04 42 90 76 20
 FAX: 04 42 90 76 21

