


Manufacturer	Source colour	Light Output Area/Length	Injection process	Input voltage
PHLOX	- LEDIR940	- BL - 50x50	- LLUB	- Q - 1R - 24V
Source type	Product type	Range	Number of light sources' rows per cicu	

PHLOX® EXCLUSIVE LIGHT PROCESS  
WORLDWIDE PATENT ISSUED

**NEW!**

# LLUB (Long life Ultra Bright) Infrared led Backlight 50x50

00000648 : PHLOX - LEDIR940 - BL - 50x50 - LLUB - Q - 1R - 24V




## Illumination

Radiance minimum	<b>≥7 W/m<sup>2</sup>.sr continuous mode</b>
Uniformity minimum	<b>≥95% (+/- 10%)</b>
Source Type	Infrared LED
Wavelength	940 nm (+/- 15)
Light Angular Distribution	30° 1/2 angle
Expected Life	<b>&gt; 100 000 hours</b>

Scan for DS and  
3D files !



## Electrical

Input Voltage	24 VDC (continuous mode)
Input Current	≤140 mA (continuous mode)
Cable length	2 M - Ø 2.7 mm (6.56 ft - Ø 0.10")
Connector	None
Cable pinout	
CE Conformity	Yes
Strobe mode	Max. Cur: 0.56 A / Pulse Width: 10ms / Duty Ratio: 1/10


## Outer unit

L x W x H	90 x 85 x 8.5 mm (3.54 x 3.35 x 0.334")
Housing Material	Black Anodized Aluminium
Weight	120 g (4.2 oz)
Mounting	4 bore holes (D7,2mm for the first 3.5 mm of height, D4 for the other 5 mm)

## Environmental

Max. Operating Humidity	95% non-condensing
Operating Temperature	50°C (122°F) max
Storage Temperature	60°C (140°F) max
Shelf life	12 months from date of purchase
Max.temp.on housing	+80°C (+176°F)

area of temperature measurement  
30mm all along the edges of the back of  
the black anodized aluminium housing  
(see image)



Do not cover the backlight when it's switched on.

## Accessories

**LED Dimmer:** 28V-5A very compact and easy to use  
Product key: PHLOX DIM LIGHT

**Power supply:** 110V and 220V  
Product key: OMRON-LED-PS-108x100x40-24V

**LED Strober:** 28V - 5A (up to 40A in pulse mode)  
Pulse width between 2µs and 10ms  
Product key: PHLOX STROBE LIGHT



CLASS 0: NO RISK (CIE S2009:2002/NF EN 62471)

**RoHS** directive compliant

Each PHLOX Backlight is provided with:

- 24 months warranty
- Certificate of uniformity
- Seal of quality on the back

January 14th 2025

LLUB Backlights by PHLOX® offer the **best life** and the **best uniformity on the market**, all in an ultra compact and **IP-63 body**.

PHLOX® is the only manufacturer to provide uniformity and radiance datas on the quality control seal positioned at the back of every backlight.


## DESIGNED

### FOR YOUR APPLICATION

- Bottle inspection (glass and plastic)
- Particle measurement
- Dimensional control
- Shaping control
- Quality control with transparency.

## & YOUR INDUSTRIAL SECTOR

- Glassmaking
- Pharmaceutical/Cosmetics
- Automotive
- Agribusiness
- Electronics
- Aeronautics and space.



PROPRIÉTÉ DE PHLOX SA- REPRODUCTION INTERDITE SAUF ACCORD ÉCRIT

00000648 : PHLOX-LEDIR940-BL-50X50-LLUB-Q-1R-24V

TEL: 04 42 90 76 20  
FAX: 04 42 90 76 21

